


Product Specifications

FlashCheck Industrial Digital Probe Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±1°F (14°F to 194°F), ±0.5°C (-10°C to 90°C) or ±1% whichever is greatest
Response Time	Less than 6 seconds between 32°F to 77°F (0°C to 25°C)
Sensor	Thermistor
Display Resolution	0.1°F/°C
Display Reading Update	Every 2 Seconds
Display Window Size	1.5in W x 0.5in H (38mm W x 12.7 mm H)
Calibration	Automatic Calibration button
Battery	Button cell alkaline
Body Casing	ABS Plastic
Probe Length	3.9in (99mm)
Probe Diameter	0.14in (3.56mm), reduced tip 0.1in (2.5mm)
Waterproof Rating	IP56
Factory Calibration	NIST traceable calibration
Compliance Certificate	Manufacturer's Certificate of Compliance, NIST traceable, CE Mark



Model 11061

- °F/°C selectable
- Automatic calibration feature
- Reduced tip probe provides less than 6 second response time
- Magnetic probe cover attaches thermometer to air vents
- Sealed unibody construction
- IP56 waterproof and grease resistant
- Probe fits standard Pete's plug self-closing valve
- Velcro strap secures thermometer to refrigerant pipes
- Automatic shut off saves battery
- High visibility yellow casing

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

Patent No.
5,709,476
5,801,968



SS 11061 18B1

