

Product Specifications

FlashLink Electronic Data Logger



| | |
|------------------------------------|--|
| Internal Temp Sensor Range | -40°F to 150°F (-40°C to 66°C) |
| External Temp Sensor Range | -40°F to 302°F (-40°C to 150°C) |
| Temperature Accuracy | ±1°F (0.5°C) at 32°F to 150°F (0°C to 66°C) ±2°F (1°C) over entire range |
| Temperature Resolution | 0.1°F/C |
| Logged Data Capacity | 7,918 data points |
| Data Download Time | 5 second typical for 3,800 data points |
| Programmable Alarm Levels | High and Low Levels over entire range |
| Startup Alarm Delay | Skip 1 to 16 points |
| Operating Alarm Delay | 0 to 79 minute delay filter |
| Logging Time Interval Range | 3 seconds to 24 hours |
| Programmable Delayed Start | 0 seconds to 256 days |
| LED Indicators | 12-second flashing red for alarm; green for active |
| Battery Type/ Life | CR2450 3v lithium/ 1 year |
| Dimensions/ Enclosure | ABS plastic case, 3.25 x 2.25 x .75 in. (8.3 x 5.7 x 1.9cm.) |
| Water Resistance | IP56 |
| Shock Resistance | Withstands 3-foot drop to hard surface |
| Certification | CE Mark by T.U.V.; Calibration Traceable to N.I.S.T. |
| Min. System Requirements | IBM compatible 486 with 4MB RAM, Windows XP or Vista |
| Software Requirements | FlashLink Program Manager Software #20223 |
| Software Requirements | FlashLink Program Manager Software #20223 |



Model 20202

- One internal sensor and one external stainless steel probe 3.5 in (89mm) with 40 in. (1m) cable
- Very easy to use and highly accurate
- Output charts, graphs, spreadsheets or email your results anywhere in the world
- Patent No. 6,088,514

DeltaTrak manufactures products under an ISO 9000 registered quality management system

SS0052 13K1

